

FIVE STATION A.D.A. WALL MOUNTED SQUARE CORNER SERVICE SINK WITH TUBULAR SUPPORTS

WITH/WITHOUT MANUAL FAUCET



| Item #: | Qty #: |
|------------|--------|
| Model #: | |
| Project #: | |





"-F" Series Sink Includes K-161-LU Gooseneck Faucets with Wrist Handles

FEATURES:

8 1/2" high backsplash.

5" sink bowl depth.

Three stainless steel "Z" brackets.

Two K-6 3 1/2" rear basket drains.

Four tubular stainless steel support brackets that allow full clearance underneath.

Manual Operated: Faucets sold separately.

"-F" Series includes five K-161-LU 3 1/2" gooseneck faucets with Wrist Handles...

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed tubular wall brackets.

Stainless steel gussets. **MECHANICAL:**

8" O.C. faucet holes punched at each station.

1 5/8" tubular "304" stainless steel wall brackets.

| | | # of Faucets Sink | # of Faucets | | Cu. |
|-----------------|--------|------------------------|-----------------------------|----------|-----|
| Model # | Length | Accommodates | Included | Wt. | Ft. |
| 19-18-100-ADA | 100" | 5 | 0 | 118 lbs. | 35 |
| | | (Faucets Not Included) | | | |
| 19-18-100-ADA-F | 100" | 5 | 5 | 128 lbs. | 35 |
| | | | (K-161-LU Faucets Included) | | |

Click Here For Install Guide

| | MULTI-STATION ACCESS | | & REPLAC | CEMENT | PARTS |
|----------------|--|------|----------------------------|-------------------|---|
| Model | Description | QTY: | | | |
| ₩ K-6 | 3 1/2" Drain (1 1/2" I.P.S.) | | | | |
| 뛝 K-13 | Stainless Steel Soap Dispenser (Wall Mount Only) | | | | |
| F K-06 | Splash Mount Faucet Mounting Kit | | | | |
| 🎁 K-101 | 8" Swing Spout Splash Mt. Faucet | | | | |
| 🎁 K-159 | Splash Mounted 3-1/2" Gooseneck Faucet (8" O.C.) | | | 9.4 | |
| 🎁 K-160 | Splash Mounted 6" Swivel Spout Faucet (8" O.C.) | | K-159 | | |
| 🎁 K-161-LU | Splash Mounted 6" Gooseneck With Wrist Handles (8" O.C.) | | | K 400 | K-161-LU |
| F K-411 | Strainer Plate for 3-1/2" Drain | | | K-160 | |
| 🎁 K-1118 | Extra H.D. 8" Splash Mounted Faucet | | | | |
| K-316-LU | Wrist Handles | | | | |
| K-472 | Faucet Hole Revision | | | | |
| | (Manual Faucet Operated Sinks Only) | | 100 | | |
| K-449 | 5" Backsplash Modification (Used When Installing A | | 0 | | |
| | Mirror Over An Ada Multi-Station Or Service Sink) | | | | |
| | Mirror Supplied By Others | | 16.40 | | K-06 |
| K-508 | Special Sizing Charge (Larger Size | | K-13 | | |
| | Cut Down To Smaller Size) | | | | |
| 🎁 TA-19 | Adjustable Stainless Steel Flanged Support Bracket | | | | |
| = Shine IIPS | | | Objects of Experience (see | In NOT CA OLD III | rd () and compliance to AD 1052 Standards |

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

DETAILS and SPECIFICATIONS

TOL ± .500" FITTINGS SUPPLIED AS SHOWN ALL DIMENSIONS ARE TYPICAL



